

Application and Safety Information

Coverage

Porous Surfaces: 100 to 400 square feet per gallon.
Two applications are recommended.

Smooth Surfaces: 500 to 1000 square feet per gallon.
Typically only one application is required.

Expected Wear: Three to 5 years on interior surfaces
and 1 to 3 years on exterior surfaces.

Application

Stir Palladion sealers thoroughly before use. Before broadly applying IT IS IMPORTANT TO TEST the sealer in a small inconspicuous area to make sure it achieves the desired sheen. This is especially important when coating highly polished or dense natural stone

FOR BEST RESULTS apply thin coats of sealer using a garden sprayer, paint pad, roller or brush. WITHIN 15 MINUTES brush or roll out to evenly distribute and coat the surface. This will remove any excess sealer that may have accumulated and provide a uniform look. A second coat may be applied after 45 minutes of drying time.

Drying and curing time will depend on temperature and humidity. Avoid moisture from rain, sprinklers and mist until dry. Surfaces can sustain light use after 6 hours and fully cure in 48 hours.

Product Characteristics

- No solvents or VOCs
- Low Odor
- Completely water soluble before dry
- Non Flammable
- Biodegradable

Shipping and Handling

DOT: Not Regulated or Hazardous
Storage Temperature: 50 - 80°F
Shelf Life – 2 years

An MSDS is available upon request



Applied Chemical Laboratories, Inc.

526 Almanor Ave.

Sunnyvale, CA 94085

Tel: 408-737-8880

Fax: 408-737-8889

E-mail: info@appchem.com

www.appchem.com

Seal and Protect Your Investment



Advanced Water-Based Polymer Sealers

Block Harmful UV and Preserve Color

Block Acids, Stains, Oil and Salt

Inhibit Algae Growth

Low Odor, No VOCs – Eco-Friendly

Easy to Apply and Maintain



**Palladion Exterior Sealers have you covered.
One product for every application — exotic stone to concrete and pavers.**

Natural, Satin and Wet Look Finishes

Your patio or driveway will look as good ten years from now as it does today

Seal and Protect: Choose Your Look:

Concrete
Stone
Pavers
Brick
Stucco
Wood

Palladion Natural Look
Maintains natural look of surface

Palladion Satin Look
Hint of sheen, intensifies color

Painted Surfaces
Bare Metal

Palladion Wet Look
High polished look, enhances color

Advanced polymer technology protects your investment in natural stone and paving surfaces.

Palladion sealers are formulated with the most advanced polymers available. They offer unsurpassed protection of your natural stone and paving surfaces by forming an



impenetrable barrier against the ravages of nature. Palladion protects and extends the beauty and integrity of natural stone, pavers, and concrete surfaces.

They also prevent rust from forming on bare metal and keep exterior wood surfaces looking like new.

Palladion's proprietary formula helps stabilize finishing sand, thereby avoiding additional material and labor costs.



What's more, Palladion sealers are non-toxic, contain no VOCs and have no odor. All of which means Palladion sealers pose no threat to the health of our children, pets — or the planet.

Easy to Us

Palladion sealers are easy to apply with a garden sprayer, paint pad, roller or brush. They go on milky white making it is easy to see where they have been applied and dry clear in just a few hours. A complete cure is usually obtained in 48 hours.

Learn more about Palladion Exterior Sealers

Talk to you local materials supplier or contact Applied Chemical Laboratories, Inc. directly at (408) 737-8880, or e-mail us at info@appchem.com

www.appchem.com

